

CA1800CX VOC Compliant Thinner


TECHNICAL DATA SHEET

Product Description

CA1800CX thinner can be used with Desoprime™ HS primers and Desothane® HS topcoats to improve spray characteristics and film appearance. CA1800CX can be used in hot weather conditions (above 29°C/85°F) to increase the wet edge of the coating.

- Zero VOC per EPA method 24
- Improves the spray characteristics at high temperatures
- Compatible with Desothane® HS topcoats
- Compatible with Desoprime™ HS primers
- Can be used in all environments including high temperature and humidity
- Service temperature -54°C to 177°C (-65°F to 350°F)

Components



- CA1800CX thinner

Specifications

CA1800CX is qualified to the following specifications:

- BAMS 565-009

CA1800CX is listed on the following application specification:

- GAMPS 3209

Note: PPG Aerospace recommends you check the most recent specification QPLs for updated information.

Product Compatibility:

CA1800CX is compatible with the following topcoat and primer specifications:

- | | |
|--------------------------------|-----------------|
| • AIMS 04-04-013 | • DMS 2115 |
| • BAMS 565-009 | • DPM 6456 |
| • BMS 10-11 Type I | • DPM 6546 |
| • BMS 10-60 Type II | • MIL-PRF-22750 |
| • BMS 10-72 Type VIII | • MIL-PRF-85285 |
| • BMS 10-79 Type II & Type III | • MMS 420 |
| • BMS 10-102 | |

CA1800CX VOC Compliant Thinner

Instructions for Use



Mixing Instructions:

CA1800CX thinner must be added at the time the base component and activator component are mixed together. Mix with Desothane[®] HS topcoat and Desoprime[™] HS primer as directed on the can label.

Add CA1800CX may be added until the desired viscosity is achieved, as long as the volume doesn't exceed the maximum listed in the note below.

CA1800CX cannot be used to reclaim a mixed coating that is near the end of its pot life.

Note: Do not add more than 25% by volume of CA1800CX to the mixed epoxy primer.

Note: Do not add more than 20% by volume of CA1800CX to the mixed polyurethane topcoat.

Note: Exceeding the recommended thinning level will cause runs and sags. When using CA1800CX during high temperature the wet edge of the coating may be reduced.

Note: It is important to condition the paint for 24 hours prior to mixing by placing all materials in the shop or hangar, with ambient temperatures between 13 ° and 35 °C (55 ° to 95 °F). The minimum temperature of the paint components should be 13 °C (55 °F) prior to mixing.



Induction Time:

Not Required

Application Guidelines

Recommended Application Conditions:

Temperature	15 - 30 °C (59 - 86 °F)
Relative Humidity	20 - 90%

These application guidelines represent PPG's best advice in standard conditions. Some parameters will be influenced by environmental conditions, equipment settings, and other variables.

CA1800CX VOC Compliant Thinner

Physical Properties (product)



Color: Clear Liquid



Gloss: Not Applicable



VOC (EPA method 24):

CA1800CX 0 grams/liter



Flash point closed cup:

CA1800CX -10 °C (15 °F)

Shelf Life:

24 months from date of manufacture for PRC-DeSoto Standard.

Note: Shelf life is provided for the original, unopened containers.

Note: The application and performance property values above are typical for the material, but not intended for use in specifications or for acceptance inspection criteria because of variations in testing methods, conditions and configurations.

Storage Recommendations



Inspect the condition of the container to ensure compliance. The material should be stored at temperatures between 5 °C to 35 °C (41 °F to 95 °F) to ensure shelf life.

Note: When procuring to a qualified material specification, follow those storage instructions.



CA1800CX VOC Compliant Thinner

Health Precautions

This product is safe to use and apply when recommended precautions are followed. Before using this product, read and understand the Safety Data Sheet (SDS), which provides information on health, physical and environmental hazards, handling precautions and first aid recommendations. An SDS is available on request. Avoid overexposure. Obtain medical care in case of extreme overexposure.

For industrial use only. Keep away from children.

Additional information can be found at: www.ppgaerospace.com

For sales and ordering information call the local PPG office at the numbers listed below:

Asia Pacific

ASC – Australia

Tel 61 (3) 9335 1557
Fax 61 (3) 9335 3490

ASC – Japan

Tel 81 561 35 5200
Fax 81 561 35 5201

ASC – South East Asia

Tel 65 6861 1119
Fax 65 6861 6162

ASC – Suzhou

Tel (86-512) 6661 5858
Fax (86-512) 6661 6868

ASC – Tianjin

Tel (86-022) 2482 8625
Fax (86-022) 2482 8600

Americas

1 (818) 362-6711 or 1-800-AEROMIX

Europe and Middle East

ASC – Central Europe

Tel 49 (40) 742 193 10
Fax 49 (40) 742 139 69

ASC – Middle East & India

Tel (971) 4 883 9666
Fax (971) 4 883 9665

ASC – North Europe

Tel 44 (0) 1388 770222
Fax 44 (0) 1388 770288

ASC – South Europe

Tel 33 (0) 235 53 43 71
Fax 33 (0) 235 53 54 44

Desoprime and Desothane are trademarks of PRC-DeSoto International, Inc.

All recommendations, statements, and technical data contained herein are based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty, either expressed or implied. User shall rely on his own information and tests to determine suitability of the product for the intended use and assumes all risks and liability resulting from his use of the product. Seller's and manufacturer's sole responsibility shall be to replace that portion of the product of this manufacturer which proves to be defective. Neither seller nor manufacturer shall be liable to the buyer or any third person for any injury, loss, or damage directly or indirectly resulting from use of, or inability to use, the product. Recommendations or statements other than those contained in a written agreement signed by an officer of the manufacturer shall not be binding upon the manufacturer or seller.

PRC-DeSoto International, Inc.

12780 San Fernando Road
Sylmar, CA 91342

www.ppgaerospace.com

Issue Date: 7/14
Lit: 2029